Author Index of Volume A24

Akiba, T., 55
Apollonov, V. V., 191
Azzouz, Y., 217

Bentley, R. E., 21
Beshkov, G. D., 61
Bitsindou, P., 181
Blom, F. R., 221
Bouwstra, S., 227
Bower, R. W., 47
Boyer, A., 217
Burgess, D., Jr., 155

Carr, W., 141
Cheeke, J. D. N., 209
Chetkin, S. A., 191
Chitnis, V. T., 123
Cho, D., 141
Chung-Chiun Liu, 213
Cichoki, A., 129
Cisse, E., 217
Clark, J. J., 107
Collins, S. D., 47
Culshaw, B., 15

Delaunay G., 181
de Weerd, E., 227
Djurić, Z., 175

Elwenspoek, M., 227

Fawcett, S. C., 5
French, P. J., 65
Fujimoto, A., 43

Goto, H., 43
Gueorguiev, V. K., 61
Guillaume, P. 181
Gunasekaran, N., 35
Grattan, K. T. V., 75

Han-Chung Wang, 239
Hasegawa, K., 55
Haskard, M. R., 163
Hirano, M., 43
Hosokawa, Y., 27

Kassabov, J., 197
Katayama, K., 55
Keltie, R. F., 5
Kobayashi, H., 27
Kreider, K. G., 155
Kumar, S. 141

Jin-Shown Shie, 203
Jiwei, J., 75

Largeau, D., 221
Lian, W., 65

Matić, M., 175
Matović, J., 175
Meggitt, B. T., 75
Middelhoek, S., 65
Mohan, S., 35
Mohanan, V., 123

Narain, R., 123
Nayak, M. M., 35
Nedev, N., 197

Palmer, A. W., 75
Petrović, R., 175
Ping Kuo Weng, 203
Popova, L. I., 61

Rajanna, K., 35
Regtien, P. P. L., 187
Roumenin, Ch. S., 83

Sakata, M., 43
Shuo Hung Chang, 239
Simičić, N., 175
Smirnov, N., 197
Smith, R. L., 47

Spangler, L. J., 117
Srivastava, K. K., 151
Steyer, A., 221
Suski, J., 221

Takahashi, Y., 55
Thornton, K. E. B., 15
Tianyou Hao, 213
Tomajova, N. A., 61

Unbehauen, R. 129
Uttamchandani, D., 15

van de Pol, F. C. M., 221
Vdovin, G. V., 191
Viens, M., 209
Villermain-Lecolier, G., 181
Vohra, A., 151
Völklein, F., 1

Wiegand, A., 1
Wise, K. D., 117
Wolffenbuttel, M. R., 187

Yanagida, H., 55
Yust, M. 155

Elsevier Sequoia/Printed in The Netherlands

Subject Index of Volume A24

Angular dispersion
  tilt sensor based on, of transmission factor of two-media interface, 191
Automotive use
  capacitance-type position sensor for, 27

Bipolar magnetotransistor sensors, 83
Bipolar technique
  study of NMOS flip-flop sensor and comparison with, 65

Cantilever beams
  optically activated $ZnO/SiO_2/Si$, 221
Capacitance-type position sensor
  for automotive use, 27
Ceramics
  high speed impact actuator using multilayer piezoelectric, 239
  humidity sensitivity of Nb_2O_5-doped TiO_2, 55

Device applications
  of new sensing material, 151
Diaphragm deflection
  experimental determination of Si pressure sensor, 175
Digital signal
  application of switched-capacitor self-oscillating circuits to conversion of *RLC* parameters into frequency or, 129
Displacement probe
  use of fiber optic, as surface finish sensor, 5

Electrically levitating micromotors
  proposal for, 141
Electrostatic motor
  miniature, 43

Fibre optic displacement probe
  use of, as surface finish sensor, 5
Fibre optic rotational monitor
  non-contact, using optical autocorrelation techniques, 75
Flip-flop sensor
  study of NMOS, and comparison with bipolar technique, 65
Flow valve
  design and fabrication of magnetically actuated micromachined, 47
Frequency signal
  application of switched-capacitor self-oscillating circuits to conversion of *RLC* parameters into, or digital signal, 129

Humidity sensitivity
  of Nb_2O_5-doped TiO_2 ceramics, 55

Impact actuator
  high speed, using multilayer piezoelectric ceramics, 239
Integrated sensors
  bulk Si SOI process for active, 117

Long-term drift
  in mineral-insulated Nicrosil-sheathed type K thermocouples, 21

Magnetic sensor
  detection of holes, rivets or screws fixed on metal sheet using flat, 181
Magnetic sensor arrays
  split-drain MOSFET, 107
Magnetosensitive transistor
  dual-emitter dual-base, 197
Magnetotransistor sensors
  bipolar, 83
Manganese
  thin-film pressure transducer with Mn film as strain gauge, 35
Metal sheet
  detection of holes, rivets or screws fixed on, using flat magnetic sensor, 181
Micromachined flow valve
  design and fabrication of magnetically actuated, 47
Micromechanical resonators
  in situ P-doped polysilicon for excitation and detection in, 227
Micromotors
  proposal for electrically levitating, 141
Miniature electrostatic motor, 43
MOSFET
  split-drain, magnetic sensor arrays, 107
Multi-layer technology
  high sensitivity and detectivity radiation thermopiles made by, 1

Nicrosil-sheathed type K thermocouples
  long-term drift in mineral-insulated, 21
Niobium
  humidity sensitivity of Nb_2O_5-doped TiO_2 ceramics, 55
NMOS flip-flop sensor
  study of, and comparison with bipolar technique, 65

Optical autocorrelation techniques
  non-contact, fibre optic rotation monitor, using, 75
Optical fiber temperature sensor
  using thermochromic solution, 213
Optically excited resonator
  pressure sensor, sensitive, 15
Optical tachometer
  revolving retro-reflective marker for, 203
Optoelectronic transducer
  for vibration amplitude measurement, 123

Elsevier Sequoia/Printed in The Netherlands

Phosphorus
in situ P-doped polysilicon for excitation and detection in micromechanical resonators, 227
Piezoelectric ceramics
high speed impact actuator using multilayer, 239
Position sensor
capacitance-type, for automotive use, 27
Pressure sensor
diaphragm deflection, experimental determination of Si, 175
sensitive optically excited resonator, 15
Pressure transducer
thin-film, with Mn films as strain gauge, 35

Radiation thermopiles
high sensitivity and detectivity, made by multi-layer technology, 1
Resonators
in situ P-doped polysilicon for excitation and detection in micromechanical resonators, 227
Revolving retro-reflective marker
for optical tachometer, 203
Rotation monitor
non-contact, fibre optic, using optical autocorrelation techniques, 75

SAW resonator oscillator
highly sensitive temperature sensor using, 209
Self-oscillating circuits
application of switched-capacitor, to conversion of *RLC* parameters into frequency or digital signal, 129
Sensing material
device applications of new, 151
Sensor design
experiment in smart, 163
Silicon
bulky Si SOI process for active integrated sensors, 117
design considerations for Si capacitive tactile cell, 187
experimental determination of Si pressure sensor diaphragm deflection, 175
optically activated $ZnO/SiO_2/Si$ cantilever beams, 221
in situ P-doped polysilicon for excitation and detection in micromechanical resonators, 227
Smart sensor design
experiment in, 163
SOI process
bulky Si, for active integrated sensors, 117
Strain gauge
thin-film pressure transducer with Mn film as, 35
Surface finish sensor
use of fiber optic displacement probe as, 5
Switched-capacitor
self-oscillating circuits, application of, to conversion of *RLC* parameters into frequency or digital signal, 129

Tachometer
revolving retro-reflective marker for optical, 203
Tactile cell
design considerations for Si capacitive, 187
Temperature sensor
highly sensitive, using SAW resonator oscillator, 209
optical fiber, using thermochromic solution, 213
Thermal response
transient, of plasma-sprayed zirconia measured with thin-film thermocouples, 155
Thermochromic solution
optical fiber temperature sensor using, 213
Thermocouples
long-term drift in mineral-insulated Nicrosil-sheathed type K, 21
transient thermal response of plasma-sprayed zirconia measured with thin-film, 155
Thermopiles
high sensitivity and detectivity radiation, made by multi-layer technology, 1
medium-power using thin-film technology, 217
Thin-film technology
medium-power thermopiles using, 217
Tilt sensor
based on angular dispersion of transmission factor of two-media interface, 191
Tin
wet etching of thin SnO_2 films, 61
Titanium
humidity sensitivity of Nb_2O_5-doped TiO_2 ceramics, 55
Transistor
magnetosensitive dual-emitter dual-base transistor, 197
Transmission factors
tilt sensor based on angular dispersion of, of two-media interface, 191

Vibration amplitude measurement
optoelectronic transducer for, 123

Wet etching
of thin SnO_2 films, 61

Zinc
optically activated $ZnO/SiO_2/Si$ cantilever beams, 221
Zirconia
transient thermal response of plasma-sprayed, measured with thin-film thermocouples, 155